

**Features**

- ★ Display Resolution D1 & Recording Resolution D1 / CIF
- ★ 2CH Audio, 4TB HDD, VGA, HDMI & 2USB
- ★ VGA High Definition output (1280 X 1024)
- ★ P2P Cloud Function



**Specification**

<b>Model</b>	<b>AX-5116P</b>
<b>System</b>	
Operating System	Embedded LINUX
<b>Video</b>	
Camera Input	16 Input BNC, 1.0V p-p, 75Ω
Preview capability	16CH D1
<b>Display</b>	
Interface	1 BNC, 1 VGA, HDMI
Audio Input / Output	2 RCA Input, 1 RCA Output
Display Resolution	PAL: 704 X 576 NTSC: 704 x 480
Display Split	1/4/8/9/16
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
<b>Recording</b>	
Recording Frame Rate	400 FPS
Playback Resolution	D1 / CIF
Play Back	16 Channel
Search prime mode	Channel number / Video Type / Date (alone or in combination queries)
USB (Backup)	Support USB / Mobile Hard Disk, FAT32 format
CMS Software	Up to 32 DVR can be connected
Compression Format	Advanced H.264 Compression
Hard Disk Capacity	4 TB SATA X 1 HDD
Recording Mode	Manual/ schedule/sensor trigger/motion detection /power-on auto record
<b>Alarm</b>	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones, Video Loss & Camera Blank
<b>Network</b>	
Network Interface	RJ45 10/100/1000Mbps adoptive Ethernet network port
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS
Client Monitoring	CMS, WebCC, Free DDNS, Cloud P2P
MAC display	Support
Smart Phone	iPhone, iPad, Android, Windows Phone
USB Port	2 USB
Control equipment	Mouse and Remote Control
<b>General</b>	
Operating Temperature	0% ~ 55%
Working humidity	10% ~ 90%
Air pressure	86kpa ~ 06kpa
Power Supply	DC 12V 2 Amps
Dimensions (W x D x H)	260x210x43mm (W *D *H)
Weight	2.3 KG without HDD (Approximately)