

Features

- ★ 8CH Display & Recording Resolution 1080P
- ★ 1CH Audio Out, 4TB HDD X 2, VGA, HDMI & 2USB
- ★ H.264/MJPEG Dual Co decoding
- ★ Support Multi-Brand Network Cameras
- ★ ONVIF Version 2.3
- ★ P2P Cloud Function



Specification

Model	AX-NVR9108P
System	
Operating System	Embedded LINUX
Video	
IP Camera Input	8 Input
Preview capability	8CH 1080P
Display	
Interface	1 BNC, 1 VGA, HDMI
Audio Input / Output	1 RCA Output
Display Resolution	1024×768, 1280×1024, 1920×1080
Display Split	1/4/8/9
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Recording	
Recording Frame Rate	5/10/15/20/25/Fps
Playback Resolution	2ch 1080P/4ch 960P/4ch 720P
Play Back	8
Search prime mode	Channel number / Video Type / Date (alone or in combination queries)
USB(Backup)	Support Usb/Mobile hard disk, FAT32 format
CMS Software	Up to 32 DVR can be connected
Compression Format	Advanced H.264 Compression
Hard Disk Capacity	4 TB
HDD Bay	2
Recording Mode	Manual/ schedule/sensor trigger/motion detection /power-on auto record
Alarm	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones, Video Loss & Camera Blank
Network	
Network Interface	RJ45 10/100/1000Mbps adoptive Ethernet network port
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS
Client Monitoring	CMS, WebCC, Free DDNS, Cloud P2P
MAC display	support
Smart Phone	iPhone, iPad, Android, Windows Phone
Peripherals	
USB Repair	support
USB port	2 port, USB2.0
Control equipment	mouse, remote control
General	
Operating Temperature	0% ~ 55%
Working humidity	10% ~ 90%
Air pressure	86kpa ~ 106kpa
Power Supply	DC 12 V
Dimensions (LxW xH)	440(w)x260(d)x50(h)mm
Weight	2 KG without HDD (Approximately)