

Features

- * 3 Mega Pixels Full HD Network IR Bullet Camera
- * 1/2.5" SONY Exmor CMOS Sensor
- * 3 Mega Pixel 6mm HD CS Lens
- * Germany Osram Infra Red ARRAY 28 μm X 3 Pcs
- * ONVIF 2.3
- * Built-in POE 802.3af
- * DWDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC
- * Advanced H.264 High profile compression
- * Support Several Servers, CMS, IP Address, DDNS, FTP, SMTP
- * Support iPhone, iPad, Android, Windows Phone
- * Support Single, Dual streams, Low streams and high resolution image
- * IP 66 Class (High Pressure Water Jets from any Direction)



Specification

Model	AXI-IPC-B30S3330
Sensor	1/2.5" SONY Exmor CMOS Sensor
Mega pixel	3 Mega pixel
Effective Pixels	2052(H) X 1536(V)
Lens	3 Mega Pixel 6mm HD CS Lens
IR LED	Germany Osram Infra Red ARRAY 28 μm X 3 Pcs
IP CLASS	IP66
IR Range Distance	30 Meters Range
IR CUT	Yes
Minimum Illumination	Color: 0.02 Lux/F1.4, B/W : 0.01Lux/F1.4; 0Lux/F1.2(IR on)
Electronic Shutter Speed	Auto/Manual, 1/3~1/10000s
Back Light Comp.	BLC / HLC / DWDR
POE	Built-in POE 802.3af
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Video Processing	H.264 Video Code, Support dual-stream, 32k-8m adjustable, 1-30/s frame rate adjustable
Video Resolution	3.0M(2048×1536) / 1080P(1920×1080) / 720P(1280×720) / D1(704×576) / CIF(352×288)
Main Stream	3M(1~15fps)/1080P/720P(1 ~ 25/30fps)
Sub Stream	D1/CIF(1 ~ 25/30fps)
Standard protocol	Onvif 2.3
Network Port	1 RJ45 Ethernet interface, 10/100M adaptation
Network Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP/Onvif
Delay	W ithin the LAN 0.3S
Frame Rate	25/30 FPS adjustable
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 24576Kbps
Video Compression	H.264/JPEG ,support AVI format.
Operation Function	Support Web setting, OSD, real-time video transmission, motive detection and IO alarm; support MJPEG capture, CMS platform
Mobile Phone Monitor	iPhone, iPad, Android, Windows Phone
Power Supply	DC 12V(AC24 optional), PoE(802.3af)
Working Temperature	.-20°C~60°C
Humidity	0% -90% RH,W ithout Condensation
Color/Material	W hite / Alloy Metal
Dimensions(W ×H×D)	95mm X 55mm X 55mm
W eight	350 Gram (Approximately)