



AXI-IPC-B30S4330

- * 4 Mega Pixels Full HD Network IR Bullet Camera
- * 1/3" SONY Exmor CMOS Sensor
- * 3 Mega Pixel 6mm HD M12 Lens
- * Germany Osram Infra Red 5µm X 36Pcs
- * Built-in POE 802.3af & *ONVIF 2.3
- * DWDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC
- * Advanced H.264 High profile compression
- * Support Several Servers, CMS, IP Address, DDNS, FTP, SMTP
- * Support iPhone, iPad, Android
- * Support Single, Dual streams, Low streams and high resolution image
- * IP 66 Class (High Pressure Water Jets from any Direction)



Specification

Model	AXI-IPC-B30S4330
Image Sensor	1/3" SONY Exmor CMOS Sensor
Mega pixel	4 Mega pixel
Effective Pixels	2688(H) X 1520(V)
Lens	3 Mega Pixel 6mm HD M12 Lens with Angle of view 85°
IR LED	Germany Osram Infra Red 5µm X 36Pcs
IR Range Distance	30 Meters Range
IP Class	IP66
Minimum Illumination	Color: 0.02 Lux/F1.4, B/W: 0.01Lux/F1.4; 0Lux/F1.2(IR on)
Electronic Shutter Speed	Auto/Manual, 1/25~1/10000s
Back Light Comp.	BLC / HLC / DWDR
PoE	Built-in PoE 802.3af
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Video Compression	H.265/H.264/JPEG,support AVI format.
Video Resolution	2688x1520/ 2048x1520/ 1920x1080/704x576/640*480/640*352/320x240
Main Stream	2688x1520(1 ~ 15) /2048x1520/ 1920x1080(1 ~ 25/30fps)
Sub Stream	704x576/640*480/640*352/320x240(1 ~ 25/30fps)
Standard protocol	Onvif 2.3
Network Port	1 RJ45 Ethernet interface, 10/100M adaptation
Network Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP/Onvif
Delay	Within the LAN 0.3S
Frame Rate	50Hz: 20fps(2688X1520), 25fps(1920 × 1080), 25fps (1280 × 960), 25fps (1280 × 720) 60Hz: 20fps(2688X1520), 30fps(1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)
Bit Rate	32KB ~16Mbps, support VBR, CBR
Video Processing	H.265/H.264 Video Code, Support dual-stream, 32k-8m adjustable,1-30/s frame rate adjustable
Operation Function	Support Web setting, OSD, real-time video transmission, motive detection and IO alarm; support MJPEG capture, CMS platform
Mobile Phone Monitor	iPhone, iPad, Android, Windows Phone
Power Supply	DC12V(AC24 optional), PoE(802.3af)
Working Temperature	-.20°C~60°C
Humidity	0%-90% RH,Without Condensation
Color/Material	White / Alloy Metal
Dimensions(W×H×D)	180mm X 65mm X 66mm
Weight	400 Gram (Approximately)

Design & Specifications are subject to change without Prior notice

Nothing Can Escape from the Altronx Eye

